Properties of a Pure, Simple Substance

A **pure substance** is one of uniform and invariable chemical composition

For our purposes a **simple substance** is taken as one for which if the values of two intensive properties are known all the other properties can be found, e.g., u = f(T,P)

P-v-T Relationship

A material can exist in the

- 1. solid phase
- 2. liquid phase
- 3. vapor (gas) phase
- **4.** a mixture of the phases at equilibrium, e.g., melting, vaporization or sublimation

Through experiments it is known that temperature and specific volume can be considered as independent and pressure determined as a function of these two: P = p(T,v)

The graph of such a function is a surface, the P-v-T surface.

P-v-T surface of a substance that contracts on freezing (common metals)



Note the step *decrease* in specific volume (step increase in density) when going from liquid to solid

P-v-T surface of a substance that expands on freezing (water)



Note the step *increase* in specific volume (step decrease in density) when going from liquid to solid

3-D surface plot not very useful, more instructive to look at 2-D projections

P-T plot for substance that expands on freezing



Only single-phase regions observed

Two-phase regions appear as lines (edge view)

Triple point represents edge view of the triple line where all three phases co-exist

P-v plot for substance that expands on freezing



The dome shaped two-phase region composed of liquid and vapor is called the **vapor (or saturation) dome**

Constant temperature lines shown in P-v plot are called **isotherms**

Above the critical point isobars and isotherms do not pass through the liquid-vapor region

The **critical point** defines the maximum pressure, i.e., above the **critical pressure** a liquid and vapor cannot coexist at equilibrium In single phase regions the state is fixed by any two of the properties P, v, T (independent)

In the two-phase regions, P and T are not independent so the state cannot be fixed by P and T but it can be fixed by P and v, or T and v



T-v plot for substance that expands on freezing (water)

Constant pressure lines are known as isobars

The **critical point** defines the maximum temperature, i.e., above the **critical temperature** a liquid and vapor cannot co-exist at equilibrium

Consider the following constant pressure heat addition process:



Characteristics of the saturation dome



The state where a phase begins, or ends is called a **saturation state**

Joining the saturation states defines the **liquid saturation line** (left of critical point) and the **vapor saturation line** (right of critical point)



Saturation Temperature – temperature of a liquid-vapor mixture at equilibrium at a pressure P^* , denoted as $T_{sat}(P^*)$

Temperature where the P* isobar crosses saturation line

Saturation Pressure – pressure of a liquid-vapor mixture at equilibrium at a temperature T^* , denoted as $P_{sat}(T^*)$

Pressure where the T* isotherm crosses the saturation line

Superheated Vapor: T* > T_{sat}(P*)



Subcooled liquid: T* < T_{sat}(P*)



Compressed liquid (same as subcooled liquid): $P^* > P_{sat}(T^*)$





Between points L and V you have a mixture of liquid and vapor at equilibrium

The mixture mass M consists of the vapor mass M_v and the liquid mass M_L , so that

$$M = M_L + M_V$$

At any point between L and V, say C, we define the vapor **quality** *x* as

$$x = \frac{\text{mass of vapor}}{\text{mass of vapor} + \text{liquid}} = \frac{M_v}{M_v + M_L}$$

Note: at point L $\rightarrow x = 0$

at point V
$$\rightarrow x = 1$$

The liquid in the mixture has properties at point L and the vapor in the mixture has properties at point V

 \therefore The mixture specific internal energy *u* is

$$M \cdot u = M_L u_L + M_V u_V$$

$$= (M - M_V)u_L + M_V u_V$$

dividing through by M

$$u = (1 - \frac{M_V}{M})u_L + \frac{M_V}{M}u_V$$

$$u = (1 - x)u_L + xu_V$$

the same applies to the other specific properties e.g., specific volume *v*

$$v = (1 - x)v_L + xv_V$$

Property Tables

Tables are used to define the relationship between P,v,T and of u. Also given are values of **enthalpy h** (= u+Pv)



Microscopic view: at equilibrium the rate of water molecules leaving liquid phase = rate of water molecules leaving liquid phase



Example:

A cylinder-piston assembly initially contains water at 3 MPa and 300° C. The water is cooled at constant volume to 200° C, then compressed isothermally to a final pressure of 2.5 MPa. Sketch the process on a T-v diagram and find the specific volume at the 3 states.



State 1:

From the saturated water (liquid-vapor) table A-3: $3MPa (30 \text{ bar}) \rightarrow T_{sat} = 233.9^{\circ}C$ since $T_1 > 233.9^{\circ}C \rightarrow$ superheated vapor

From the superheated water vapor table A-4: 3MPa and $300^{\circ}C \rightarrow v_1 = 0.0811 \text{ m}^3/\text{kg}$

State 2:

Cool at constant volume, so $v_2 = v_1 = 0.0811 \text{ m}^3/\text{kg}$

From the saturated water (liquid-vapor) table A-2: $200^{\circ}C \rightarrow v_{L} = .001157 \text{m}^{3}/\text{kg}, v_{V} = .1274 \text{ m}^{3}/\text{kg}$ because $v_{L} < v_{2} < v_{V}$ we have a liquid vapor mixture

recall, $v = (1-x) v_L + x v_V$

 $= \mathbf{v}_{\mathrm{L}} + x \left(\mathbf{v}_{\mathrm{V}} - \mathbf{v}_{\mathrm{L}} \right)$

 $v_2 = v_1 = 0.0811 = .0001157 + x (.1279 - .0001157)$

x= 0.633 i.e., 63.3% vapor by mass

State 3:

Compress isothermally to 2.5 MPa, so $T_3 = T_2 = 200^{\circ}C$

From the compressed liquid water table A-5: 200°C and 2.5 MPa \rightarrow v₃= 1.155x10⁻³ m³/kg

		Specific Volume m ³ /kg		Internal Energy kJ/kg		Enthalpy kJ/kg			Entropy kJ/kg K		
Temp. C	Press. bar	Sat. Liquid v _f 10 ³	Sat. Vapor v _g	Sat. Liquid <i>u_t</i>	Sat. Vapor <i>u_g</i>	Sat. Liquid h _t	Evap. h_{fg}	Sat. Vapor h _s	Sat. Liquid s _f	Sat. Vapor s _g	Temp. C
.01	0.00611	1.0002	206.136	0.00	2375.3	0.01	2501.3	2501.4	0.0000	9.1562	.01
4	0.00813	1.0001	157.232	16.77	2380.9	16.78	2491.9	2508.7	0.0610	9.0514	4
5	0.00872	1.0001	147.120	20.97	2382.3	20.98	2489.6	2510.6	0.0761	9.0257	5
6	0.00935	1.0001	137.734	25.19	2383.6	25.20	2487.2	2512.4	0.0912	9.0003	6
8	0.01072	1.0002	120.917	33.59	2386.4	33,60	2482.5	2516.1	0.1212	8.9501	8
10	0.01228	1.0004	106.379	42.00	2389.2	42.01	2477.7	2519.8	0.1510	8.9008	10
11	0.01312	1.0004	99.857	46.20	2390.5	46.20	2475.4	2521.6	0.1658	8.8765	11
12	0.01402	1.0005	93.784	50.41	2391.9	50.41	2473.0	2523.4	0.1806	8.8524	12
13	0.01497	1.0007	88.124	54.60	2393.3	54.60	2470.7	2525.3	0.1953	8.8285	13
14	0.01598	1.0008	82.848	58.79	2394.7	58.80	2468.3	2527.1	0.2099	8.8048	14
15	0.01705	1.0009	77.926	62.99	2396.1	62.99	2465.9	2528.9	0.2245	8.7814	15
16	0.01818	1.0011	73.333	67.18	2397.4	67.19	2463.6	2530.8	0.2390	8.7582	16
17	0.01938	1.0012	69.044	71.38	2398.8	71.38	2461.2	2532.6	0.2535	8.7351	17
18	0.02064	1.0014	65.038	75.57	2400.2	75.58	2458.8	2534.4	0.2679	8.7123	18
19	0.02198	1.0016	61.293	79.76	2401.6	79.77	2456.5	2536.2	0.2823	8.6897	19
20	0.02339	1.0018	57.791	83.95	2402.9	83.96	2454.1	2538.1	0.2966	8.6672	20
21	0.02487	1.0020	54.514	88.14	2404.3	88.14	2451.8	2539.9	0.3109	8.6450	21
22	0.02645	1.0022	51.447	92.32	2405.7	92.33	2449.4	2541.7	0.3251	8.6229	22
23	0.02810	1.0024	48.574	96.51	2407.0	96.52	2447.0	2543.5	0.3393	8.6011	23
24	0.02985	1.0027	45.883	100.70	2408.4	100.70	2444.7	2545.4	0.3534	8.5794	24
25	0.03169	1.0029	43.360	104.88	2409.8	104.89	2442.3	2547.2	0.3674	8.5580	25
26	0.03363	1.0032	40,994	109.06	2411.1	109.07	2439.9	2549.0	0.3814	8.5367	26
27	0.03567	1.0035	38.774	113.25	2412.5	113.25	2437.6	2550.8	0.3954	8.5156	27
28	0.03782	1.0037	36.690	117.42	2413.9	117.43	2435.2	2552.6	0.4093	8.4946	28
29	0.04008	1.0040	34.733	121.60	2415.2	121.61	2432.8	2554.5	0.4231	8.4739	29
30	0.04246	1.0043	32.894	125.78	2416.6	125,79	2430.5	2556.3	0.4369	8.4533	30
31	0.04496	1.0046	31.165	129.96	2418.0	129.97	2428.1	2558.1	0.4507	8.4329	31
32	0.04759	1.0050	29.540	134.14	2419.3	134.15	2425.7	2559.9	0.4644	8.4127	32
33	0.05034	1.0053	28.011	138.32	2420.7	138.33	2423.4	2561.7	0.4781	8.3927	33
34	0.05324	1.0056	26.571	142.50	2422.0	142.50	2421.0	2563.5	0.4917	8.3728	34
35	0.05628	1.0060	25.216	146.67	2423.4	146.68	2418.6	2565.3	0.5053	8.3531	35
36	0.05947	1.0063	23.940	150.85	2424.7	150.86	2416.2	2567.1	0.5188	8.3336	36
38	0.06632	1.0071	21.602	159.20	2427.4	159.21	2411.5	2570.7	0.5458	8.2950	38
40	0.07384	1.0078	19.523	167.56	2430.1	167.57	2406.7	2574.3	0.5725	8.2570	40
45	0.09593	1.0099	15.258	188.44	2436.8	188.45	2394.8	2583.2	0.6387	8.1648	45

TableA-2 Properties of Saturated Water (Liquid-Vapor): Temperature Table

		Specifi	c Volume 1 ³ /kg	Internal kJ/	Energy kg		Enthalpy kJ/kg		Entr kJ/kş	ropy g K	
Temp. C	Press. bar	Sat. Liquid $v_f = 10^3$	Sat. Vapor _{Ug}	Sat. Liquid <i>u</i> r	Sat. Vapor ug	Sat. Liquid h _f	Evap. h _{is}	Sat. Vapor h _g	Sat. Liquid s _f	Sat. Vapor <i>s</i> g	Temp. C
50	.1235	1.0121	12.032	209.32	2443.5	209.33	2382.7	2592.1	.7038	8.0763	50
55	.1576	1.0146	9.568	230.21	2450.1	230.23	2370.7	2600.9	.7679	7.9913	55
60	.1994	1.0172	7.671	251.11	2456.6	251.13	2358.5	2609.6	.8312	7.9096	60
65	.2503	1.0199	6.197	272.02	2463.1	272.06	2346.2	2618.3	.8935	7.8310	65
70	.3119	1.0228	5.042	292.95	2469.6	292.98	2333.8	2626.8	.9549	7.7553	70
75	.3858	1.0259	4.131	313.90	2475.9	313.93	2321.4	2635.3	1.0155	7.6824	75
80	.4739	1.0291	3.407	334.86	2482.2	334.91	2308.8	2643.7	1.0753	7.6122	80
85	.5783	1.0325	2.828	355.84	2488.4	355.90	2296.0	2651.9	1.1343	7.5445	85
90	.7014	1.0360	2.361	376.85	2494.5	376.92	2283.2	2660.1	1.1925	7.4791	90
95	.8455	1.0397	1.982	397.88	2500.6	397.96	2270.2	2668.1	1.2500	7.4159	95
100	1.014	1.0435	1.673	418.94	2506.5	419.04	2257.0	2676.1	1.3069	7.3549	100
110	1.433	1.0516	1.210	461.14	2518.1	461.30	2230.2	2691.5	1.4185	7.2387	110
120	1.985	1.0603	0.8919	503.50	2529.3	503.71	2202.6	2706.3	1.5276	7.1296	120
130	2.701	1.0697	0.6685	546.02	2539.9	546.31	2174.2	2720.5	1.6344	7.0269	130
140	3.613	1.0797	0.5089	588.74	2550.0	589.13	2144.7	2733.9	1.7391	6.9299	140
150	4.758	1.0905	0.3928	631.68	2559.5	632.20	2114.3	2746.5	1.8418	6.8379	150
160	6.178	1.1020	0.3071	674.86	2568.4	675.55	2082.6	2758.1	1.9427	6.7502	160
170	7.917	1.1143	0.2428	718.33	2576.5	719.21	2049.5	2768.7	2.0419	6.6663	170
180	10.02	1.1274	0.1941	762.09	2583.7	763.22	2015.0	2778.2	2.1396	6.5857	180
190	12.54	1.1414	0.1565	806.19	2590.0	807.62	1978.8	2786.4	2.2359	6.5079	190
200	15.54	1.1565	0.1274	850.65	2595.3	852.45	1940.7	2793.2	2.3309	6.4323	200
210	19.06	1.1726	0.1044	895.53	2599.5	897.76	1900.7	2798.5	2.4248	6.3585	210
220	23.18	1.1900	0.08619	940.87	2602.4	943.62	1858.5	2802.1	2.5178	6.2861	220
230	27.95	1.2088	0.07158	986.74	2603.9	990.12	1813.8	2804.0	2.6099	6.2146	230
240	33.44	1.2291	0.05976	1033.2	2604.0	1037.3	1766.5	2803.8	2.7015	6.1437	240
250	39.73	1.2512	0.05013	1080.4	2602.4	1085.4	1716.2	2801.5	2.7927	6.0730	250
260	46.88	1.2755	0.04221	1128.4	2599.0	1134.4	1662.5	2796.6	2.8838	6.0019	260
270	54.99	1.3023	0.03564	1177.4	2593.7	1184.5	1605.2	2789.7	2.9751	5.9301	270
280	64.12	1.3321	0.03017	1227.5	2586.1	1236.0	1543.6	2779.6	3.0668	5.8571	280
290	74.36	1.3656	0.02557	1278.9	2576.0	1289.1	1477.1	2766.2	3.1594	5.7821	290
300	85.81	1.4036	0.02167	1332.0	2563.0	1344.0	1404.9	2749.0	3.2534	5.7045	300
320	112.7	1.4988	0.01549	1444.6	2525.5	1461.5	1238.6	2700.1	3.4480	5.5362	320
340	145.9	1.6379	0.01080	1570.3	2464.6	1594.2	1027.9	2622.0	3.6594	5.3357	340
360	186.5	1.8925	0.006945	1725.2	2351.5	1760.5	720.5	2481.0	3.9147	5.0526	360
374.14	220.9	3.155	0.003155	2029.6	2029.6	2099.3	0	2099.3	4.4298	4.4298	374.14

TableA-2 (Continued)

Source: Tables A-2 through A-5 are extracted from I H. Keenan, F. G. Keyes, P. G. Hill, and I G. Moore, Steam Tables, Wiley, New York, 1969.

		Specific Volume m ³ /kg		Internal Energy kJ/kg		Enthalpy kJ/kg			Entropy kJ/kg K		
Press. bar	Temp. C	Sat. Liquid v _f 10 ³	Sat. Vapor v _s	Sat. Liquid u _t	Sat. Vapor u _s	Sat. Liquid <i>h</i> t	Evap. h _{fg}	Sat. Vapor h_{g}	Sat. Liquid s _i	Sat. Vapor s _g	Press. bar
0.04	28.96	1.0040	34.800	121.45	2415.2	121.46	2432.9	2554.4	0.4226	8.4746	0.04
0.06	36.16	1.0064	23.739	151.53	2425.0	151.53	2415.9	2567.4	0.5210	8.3304	0.06
0.08	41.51	1.0084	18.103	173.87	2432.2	173.88	2403.1	2577.0	0.5926	8.2287	0.08
0.10	45.81	1.0102	14.674	191.82	2437.9	191.83	2392.8	2584.7	0.6493	8.1502	0.10
0.20	60.06	1.0172	7.649	251.38	2456.7	251.40	2358.3	2609.7	0.8320	7.9085	0.20
0.30	69.10	1.0223	5.229	289.20	2468.4	289.23	2336.1	2625.3	0.9439	7.7686	0.30
0.40	75.87	1.0265	3.993	317.53	2477.0	317.58	2319.2	2636.8	1.0259	7.6700	0.40
0.50	81.33	1.0300	3.240	340.44	2483.9	340.49	2305.4	2645.9	1.0910	7.5939	0.50
0.60	85.94	1.0331	2.732	359.79	2489.6	359.86	2293.6	2653.5	1.1453	7.5320	0.60
0.70	89.95	1.0360	2.365	376.63	2494.5	376.70	2283.3	2660.0	1.1919	7.4797	0.70
0.80	93.50	1.0380	2.087	391.58	2498.8	391.66	2274.1	2665.8	1.2329	7.4346	0.80
0.90	96.71	1.0410	1.869	405.06	2502.6	405.15	2265.7	2670.9	1.2695	7.3949	0.90
1.00	99.63	1.0432	1.694	417.36	2506.1	417.46	2258.0	2675.5	1.3026	7.3594	1.00
1.50	111.4	1.0528	1.159	466.94	2519.7	467.11	2226.5	2693.6	1.4336	7.2233	1.50
2.00	120.2	1.0605	0.8857	504.49	2529.5	504.70	2201.9	2706.7	1.5301	7.1271	2.00
2.50	127.4	1.0672	0.7187	535.10	2537.2	535.37	2181.5	2716.9	1.6072	7.0527	2.50
3.00	133.6	1.0732	0.6058	561.15	2543.6	561.47	2163.8	2725.3	1.6718	6.9919	3.00
3.50	138.9	1.0786	0.5243	583.95	2546.9	584.33	2148.1	2732.4	1.7275	6.9405	3.50
4.00	143.6	1.0836	0.4625	604.31	2553.6	604.74	2133.8	2738.6	1.7766	6.8959	4.00
4.50	147.9	1.0882	0.4140	622.25	2557.6	623,25	2120.7	2743.9	1.8207	6.8565	4.50
5.00	151.9	1.0926	0.3749	639.68	2561.2	640.23	2108.5	2748.7	1.8607	6.8212	5.00
6.00	158.9	1.1006	0.3157	669.90	2567.4	670.56	2086.3	2756.8	1.9312	6.7600	6.00
7.00	165.0	1.1080	0.2729	696.44	2572.5	697.22	2066.3	2763.5	1.9922	6.7080	7.00
8.00	170.4	1.1148	0.2404	720.22	2576.8	721.11	2048.0	2769.1	2.0462	6.6628	8.00
9.00	175.4	1.1212	0.2150	741.83	2580.5	742.83	2031.1	2773.9	2.0946	6.6226	9.00
10.0	179.9	1.1273	0.1944	761.68	2583.6	762.81	2015.3	2778.1	2.1387	6.5863	10.0
15.0	198.3	1.1539	0.1318	843.16	2594.5	844.84	1947.3	2792.2	2.3150	6.4448	15.0
20.0	212.4	1.1767	0.09963	906.44	2600.3	908.79	1890.7	2799.5	2.4474	6.3409	20.0
25.0	224.0	1.1973	0.07998	959.11	2603.1	962.11	1841.0	2803.1	2.5547	6.2575	25.0
30.0	233.9	1.2165	0.06668	1004.8	2604.1	1008.4	1795.7	2804.2	2.6457	6.1869	30.0
35.0	242.6	1.2347	0.05707	1045.4	2603.7	1049.8	1753.7	2803.4	2.7253	6.1253	35.0
40.0	250.4	1.2522	0.04978	1082.3	2602.3	1087.3	1714.1	2801.4	2.7964	6.0701	40.0
45.0	257.5	1.2692	0.04406	1116.2	2600.1	1121.9	1676.4	2798.3	2.8610	6.0199	45.0
50.0	264.0	1.2859	0.03944	1147.8	2597.1	1154.2	1640.1	2794.3	2.9202	5.9734	50.0
60.0	275.6	1.3187	0.03244	1205.4	2589.7	1213.4	1571.0	2784.3	3.0267	5.8892	60.0
70.0	285.9	1.3513	0.02737	1257.6	2580.5	1267.0	1505.1	2772.1	3.1211	5.8133	70.0
80.0	295.1	1.3842	0.02352	1305.6	2569.8	1316.6	1441.3	2758.0	3.2068	5.7432	80.0
90.0	303.4	1.4178	0.02048	1350.5	2557.8	1363.3	1378.9	2742.1	3.2858	5.6772	90.0
100.	311.1	1.4524	0.01803	1393.0	2544.4	1407.6	1317.1	2724.7	3.3596	5.6141	100.
110.	318.2	1.4886	0.01599	1433.7	2529.8	1450.1	1255.5	2705.6	3.4295	5.5527	110.

Table A-3 Properties of Saturated Water (Liquid-Vapor): Pressure Table

TalleA-3 (Continued)

		Specific m	Volume ³ /kg	Internal kJ/	Energy kg		Enthalpy kJ/kg		Entr kJ/kş	ropy g K	
Press. Tem bar C	Temp. C	Sat. Liquid v _f 10 ³	Sat. Vapor Dg	Sat. Liquid _{Ut}	Sat. Vapor u _s	Sat. Liquid h _t	Evap. h _{ig}	Sat. Vapor h _g	Sat. Liquid s _t	Sat. Vapor s _s	Press. bar
120.	324.8	1.5267	0.01426	1473.0	2513.7	1491.3	1193.6	2684.9	3,4962	5.4924	120.
130.	330.9	1.5671	0.01278	1511.1	2496.1	1531.5	1130.7	2662.2	3.5606	5.4323	130.
140.	336.8	1.6107	0.01149	1548.6	2476.8	1571.1	1066.5	2637.6	3.6232	5.3717	140.
150.	342.2	1.6581	0.01034	1585.6	2455.5	1610.5	1000.0	2610.5	3.6848	5.3098	150.
160.	347.4	1.7107	0.009306	1622.7	2431.7	1650.1	930.6	2580.6	3.7461	5.2455	160.
170.	352.4	1.7702	0.008364	1660.2	2405.0	1690.3	856.9	2547.2	3.8079	5.1777	170.
180.	357.1	1.8397	0.007489	1698.9	2374.3	1732.0	777.1	2509.1	3.8715	5.1044	180.
190.	361.5	1.9243	0.006657	1739.9	2338.1	1776.5	688.0	2464.5	3.9388	5.0228	190.
200.	365.8	2.036	0.005834	1785.6	2293.0	1826.3	583.4	2409.7	4.0139	4.9269	200.
220.9	374.1	3.155	0.003155	2029.6	2029.6	2099.3	0	2099.3	4.4298	4.4298	220.9

Т	υ	34	h	S	v	14	h	5
°C	m³/kg	kJ/kg	kJ/kg	kJ/kg · K	m³/kg	kJ/kg	kJ/kg	kJ/kg · K
	р	= 0.06 ba	r = 0.006	MPa	р	= 0.35 ba	r = 0.035	MPa
		$(1_{sat} =$	= 30.10°C)			$(1_{sat} =$	= 12.09°C)	
Sat.	23.739	2425.0	2567.4	8.3304	4.526	2473.0	2631.4	7.7158
80	27.132	2487.3	2650.1	8.5804	4.625	2483.7	2645.6	7.7564
120	30.219	2544.7	2726.0	8.7840	5.163	2542.4	2723.1	7.9644
160	33.302	2602.7	2802.5	8,9693	5.696	2601.2	2800.6	8.1519
200	36.383	2661.4	2879.7	9.1398	6.228	2660.4	2878.4	8.3237
240	39.462	2721.0	2957.8	9.2982	6.758	2720.3	2956.8	8.4828
280	42.540	2781.5	3036.8	9.4464	7.287	2780.9	3036.0	8.6314
320	45.618	2843.0	3116.7	9.5859	7.815	2842.5	3116.1	8.7712
360	48.696	2905.5	3197.7	9.7180	8.344	2905.1	3197.1	8.9034
400	51.774	2969.0	3279.6	9.8435	8.872	2968.6	3279.2	9.0291
440	54.851	3033.5	3362.6	9.9633	9.400	3033.2	3362.2	9.1490
500	59.467	3132.3	3489.1	10.1336	10.192	3132.1	3488.8	9.3194

TableA-4 Properties of Superheated Water Vapor

	p = 0.70 bar = 0.07 MPa $(T_{sat} = 89.95^{\circ}\text{C})$								
Sat.	2.365	2494.5	2660.0	7.4797					
100	2.434	2509.7	2680.0	7.5341					
120	2.571	2539.7	2719.6	7.6375					
160	2.841	2599.4	2798.2	7.8279					
200	3.108	2659.1	2876.7	8.0012					
240	3.374	2719.3	2955.5	8.1611					
280	3.640	2780.2	3035.0	8.3162					
320	3.905	2842.0	3115.3	8.4504					
360	4.170	2904.6	3196.5	8.5828					
400	4.434	2968.2	3278.6	8.7086					
440	4.698	3032.9	3361.8	8.8286					
500	5.095	3131.8	3488.5	8,9991					

1.694	2506.1	2675.5	7.3594
1.696	2506.7	2676.2	7.3614
1.793	2537.3	2716.6	7.4668
1.984	2597.8	2796.2	7.6597
2.172	2658.1	2875.3	7.8343
2.359	2718.5	2954.5	7.9949
2.546	2779.6	3034.2	8.1445
2.732	2841.5	3114.6	8.2849
2.917	2904.2	3195.9	8.4175
3.103	2967.9	3278.2	8.5435
3.288	3032.6	3361.4	8.6636
3.565	3131.6	3488.1	8.8342

p = 5 1.5 bar = 0.15 MPa ($T_{\rm at} = 111.37$ °C)					p = 5 3.0 bar = 5 0.30 MPa ($T_{rat} = 133.55$ °C)				
Sat.	1.159	2519.7	2693.6	7.2233	0.606	2543.6	2725.3	6.9919	
120	1.188	2533.3	2711.4	7.2693					
160	1.317	2595.2	2792.8	7.4665	0.651	2587.1	2782.3	7.1276	
200	1.444	2656.2	2872.9	7.6433	0.716	2650.7	2865.5	7.3115	
240	1.570	2717.2	2952.7	7.8052	0.781	2713.1	2947.3	7.4774	
280	1.695	2778.6	3032.8	7.9555	0.844	2775.4	3028.6	7.6299	
320	1.819	2840.6	3113.5	8.0964	0.907	2838.1	3110.1	7.7722	
360	1.943	2903.5	3195.0	8.2293	0.969	2901.4	3192.2	7.9061	
400	2.067	2967.3	3277.4	8.3555	1.032	2965.6	3275.0	8.0330	
440	2.191	3032.1	3360.7	8.4757	1.094	3030.6	3358.7	8.1538	
500	2.376	3131.2	3487.6	8.6466	1.187	3130.0	3486.0	8.3251	
600	2.685	3301.7	3704.3	8.9101	1.341	3300.8	3703.2	8.5892	

The	102	cities of c	, ompresse	d Liquid Wate	103		1	
I C	0 10°	u h Lara	h	S LIKA K	U 10°	11 Inter	h	S kilka K
0	m /kg	KJ/Kg	KJ/Kg	KJ/Kg K	m/kg	KJ/Kg	RJ/Kg	KJ/Kg K
	1	25 bas	r 2.5 M	Pa		p 50 ba	r 5.0 M	Pa
		$(T_{\rm sat})$	223.99 C)			$(T_{\rm sat})$	263.99 C)	
20	1.0006	83.80	86.30	.2961	.9995	83.65	88.65	.2956
40	1.0067	167.25	169.77	.5715	1.0056	166.95	171.97	.5705
80	1.0280	334.29	336.86	1.0737	1.0268	333.72	338.85	1.0720
100	1.0423	418.24	420.85	1.3050	1.0410	417.52	422.72	1.3030
140	1.0784	587.82	590.52	1.7369	1.0768	586.76	592.15	1.7343
180	1.1261	761.16	763.97	2.1375	1.1240	759.63	765.25	2.1341
200	1.1555	849.9	852.8	2.3294	1.1530	848.1	853.9	2.3255
220	1.1898	940.7	943.7	2.5174	1.1866	938.4	944.4	2.5128
Sat.	1.1973	959.1	962.1	2.5546	1.2859	1147.8	1154.2	2.9202

TABLEA-S Properties of Compressed Liquid Water

		p = 75 ba (T_{sat})	r 7.5 MF 290.59 C))a
20	.9984	83.50	90.99	.2950
40	1.0045	166.64	174.18	.5696
80	1.0256	333.15	340.84	1.0704
100	1.0397	416.81	424.62	1.3011
140	1.0752	585.72	593.78	1.7317
180	1.1219	758.13	766.55	2.1308
220	1.1835	936.2	945.1	2.5083
260	1.2696	1124.4	1134.0	2.8763
Sat.	1.3677	1282.0	1292.2	3.1649

I) 100 ba	r 10.0 M	Pa
	(1 sat	511.00 C)	
.9972	83.36	93.33	.2945
1.0034	166.35	176.38	.5686
1.0245	332.59	342.83	1.0688
1.0385	416.12	426.50	1.2992
1.0737	584.68	595.42	1.7292
1.1199	756.65	767.84	2.1275
1.1805	934.1	945.9	2.5039
1.2645	1121.1	1133.7	2.8699
1.4524	1393.0	1407.6	3.3596

	p 150 bar 15.0 MPa (T 242.24 C)							
20	.9950	83.06	97.99	.2934				
40	1.0013	165.76	180.78	.5666				
80	1.0222	331.48	346.81	1.0656				
100	1.0361	414.74	430.28	1.2955				
140	1.0707	582.66	598.72	1.7242				
180	1.1159	753.76	770.50	2.1210				
220	1.1748	929.9	947.5	2.4953				
260	1.2550	1114.6	1133.4	2.8576				
300	1.3770	1316.6	1337.3	3.2260				
Sat.	1.6581	1585.6	1610.5	3.6848				

p = 200 bar = 20.0 MPa ($T_{sat} = 365.81 \text{ C}$)								
.9928	82.77	102.62	.2923					
.9992	165.17	185.16	.5646					
1.0199	330.40	350.80	1.0624					
1.0337	413.39	434.06	1.2917					
1.0678	580.69	602.04	1.7193					
1.1120	750.95	773.20	2.1147					
1.1693	925.9	949.3	2.4870					
1.2462	1108.6	1133.5	2.8459					
1.3596	1306.1	1333.3	3.2071					
2.036	1785.6	1826.3	4.0139					

		p 250 b	50 bar 25 MPa		p 300 bar 30.0 MPa			
20	.9907	82.47	107.24	.2911	.9886	82.17	111.84	.2899
40	.9971	164.60	189.52	.5626	.9951	164.04	193.89	.5607
100	1.0313	412.08	437.85	1.2881	1.0290	410.78	441.66	1.2844
200	1.1344	834.5	862.8	2.2961	1.1302	831.4	865.3	2.2893
300	1.3442	1296.6	1330.2	3.1900	1.3304	1287.9	1327.8	3.1741



Refer to graph above and compressed liquid tables and note v and u change very little with pressure at a fixed temperature, say T*

Therefore, a reasonable assumption for engineering calculations is:

$$v(T,P)=v_L(T)$$
$$u(T,P)=u_L(T)$$

For example, if you have a tank partially filled with water and air, if you increase the air pressure the water level does not drop that much \rightarrow specific volume remains roughly constant